

Materials of Construction

Cartridge Case:	Polypropylene
Carbon Block Media:	Coconut Activated Carbon
O-Rings:	Silicone

Construction Notes

1. Double O-Ring Seal ensures a reliable and leak free secure connection.
2. Cartridges release with a quarter turn, which automatically shuts off the water supply during changeout.

Technical Data

Micron Rating (µ)	1
Height (")	10
Width (")	2.5
Maximum Operating Temperature (°C)	38
Maximum Operating Pressure (bar)	6.9
Capacity (litres)	9,500
Flow Rate (lpm)	3.8



Available Head Options



Single Head
PTL-FH1



Double Head
PTL-FH2

System Height Including Head (")	12
Head Inlet/Outlet Ports (")	1/4

Point-Of-Use Range

Also available from the SPECTRUM Twist-Lock family:

- Premier Twist-Lock Reverse Osmosis Systems (PTL-ROSYSTEM)
- Premier Twist-Lock Carbon Block (PTL-CB)
- Premier Twist-Lock Hollow Fibre (PTL-HF)
- Premier Twist-Lock Reverse Osmosis Membrane (PTL-RO)
- Premier Twist-Lock Sediment (PTL-S)
- Premier Twist-Lock Filter Heads (PTL-FH1 & PTL-FH2)