

# PREMIER TWIST-LOCK SEDIMENT PTL-S

## Materials of Construction

Cartridge Case:	Polypropylene
Sediment Media:	Spun Bonded Polypropylene
O-Rings:	Silicone

## Construction Notes

1. Double O-Ring Seal ensures a reliable and leak free secure connection.
2. Cartridges release with a quarter turn, which automatically shuts off the water supply during changeout.

## Technical Data

Micron Rating ( $\mu$ )	5
Length (")	10
Width (")	2.5
Maximum Operating Temperature ( $^{\circ}$ C)	38
Maximum Operating Pressure (bar)	6.9
Capacity (litres)	9,500
Flow Rate (lpm)	3.8



## Available Head Options



Single Head  
PTL-FH1



Double Head  
PTL-FH2

System Height Including Head (")	12
Head Inlet/Outlet Ports (")	1/4

## Point-Of-Use Range

Also available from the SPECTRUM Twist-Lock family:

- Premier Twist-Lock Reverse Osmosis System (PTL-ROSYSTEM)
- Premier Twist-Lock Carbon Block (PTL-CB)
- Premier Twist-Lock Hollow Fibre (PTL-HF)
- Premier Twist-Lock Reverse Osmosis Membrane (PTL-RO)
- Premier Twist-Lock Sediment (PTL-S)
- Premier Twist-Lock Filter Heads (PTL-FH1/2)